



MORSETTI / CLAMPS



267.612.177 (Ø22 1/2)
267.612.1 (Ø20)




267.612.17 (Ø22 1/2)
267.612.17 20 (Ø20)



267.612.178



267.612.18



◀ PAGE 19/46 ▶

Standard nichelati - completi di viti inox e O Ring

Pressione di esercizio max.: 50 bar

Peso: 267.612.1 65 g - 267.612.177 62 g - 267.612.17 20 70 g - 267.612.17 70 g - 267.612.178 67 g - 267.612.18 75 g

Materiali: ottone nichelato - acciaio inox - NBR

Impiego: su gruppi da diserbo ed atomizzatori. Leggeri e resistenti consentono il montaggio di getti, ugelli e manometri.

Standard nickel plated with stainless steel screws and O Ring

Max. operating pressure: 50 bar / 725 psi

Weight: 267.612.177 62 g / 2.2 oz - 267.612.17 70 g / 2.5 oz - 267.612.178 67 g / 2.4 oz - 267.612.18 75 g / 2.6 oz
267.612.1 65 g / 2,29 oz - 267.612.17 20 g / 2,47 oz

Materials: nickel plated brass - stainless steel - Buna N

Use: on booms and air blast sprayers. Light and resistant. For nozzles, spray tips and pressure gauges.

COME SI ORDINA / HOW TO ORDER

CODICE code	Ø1 mm	Ø2 mm	FILETTATURA thread	FILETTATURA CAVALLOTTO clamp thread	A mm	B mm	
267.612.1	Ø20	Ø7			275		
267.612.177	Ø22 - Ø21.3	Ø7			275		
267.612.17	Ø22 - Ø21.3	Ø7			35		
267.612.17 20	Ø20	Ø7			35	42	25
267.612.178	Ø22 - Ø21.3	Ø7	G1/4F. 1/4" BSPF.	M8	275		
267.612.18	Ø22 - Ø21.3	Ø7		M8	35		



GETTI
NOZZLES



CATALOGHI
CATALOGUES



IMMAGINI
HI-RES PICTURES



RICAMBI
SPARE PARTS :

267.612.1
267.612.17
267.612.17 20

267.612.18
267.612.177
267.612.178