




M79



PAGE 44/46

**Standard completo di cavallotto, viti inox, membrana FPM, O Ring, ghiera G3/8, filtri a fessura
Ugelli non compresi**

Pressione di esercizio max.: 30 bar
Apertura antigoccia: 1 bar
Peso: 290 g

Materiali: ottone nichelato - acciaio inox - NBR - PA66 - FPM

Impiego: su barre diserbanti. Ingombri ridotti. Due ugelli selezionabili con posizioni intermedie di chiusura. Eccellente resistenza alla pressione ed agli urti. Indicato per trattamenti che richiedono elevata penetrazione fogliare.

**Standard with clamp, stainless steel screws, FKM diaphragm, O Ring, 3/8" BSP cap, slotted strainers
Spray tips not included**

Max. operating pressure.: 30 bar / 450 psi
Antidrip opens at 1 bar / 15 psi
Weight: 290 g / 10.2 oz

Materials: nickel plated brass - stainless steel - Buna N - PA66 - FKM

Use: on crop protection booms. Compact. Rollover with two shut off positions. Pressure and shock proof. For high pressure on post emergence.

COME SI ORDINA / HOW TO ORDER

CODICE code	Ø1 mm	Ø2 mm	A mm	B mm	C mm	D mm		KIT RICAMBIO spare parts kit
79.617.3	1/2" (Ø21.3) - Ø22	Ø7	66	15	38	42	10	75.302.28



GETTI
NOZZLES



UGELLI
SPRAY TIPS



COMPONENTI
PARTS



CATALOGHI
CATALOGUES



IMMAGINI
HI-RES PICTURES



RICAMBI
SPARE PARTS :

79.617.3