



# LAVAGGIO / WASHING




22.901.161



22.1617.11  
22.1617.73  
sotto insieme lavaggio  
washing subassembly

◀ PAGE 09/25 ▶



- 22.901.161** standard con ugello M15x1 Ø1.5 - attacco G1/2M.
- 22.1617.11** standard senza ugello - attacco G1/4M. per impugnature PA-ETL - attacco ugello M15x1
- 22.1617.73** standard senza ugello - attacco G1/4M. per impugnature Mecline - attacco ugello M15x1

Foro max. ugello: Ø2.3  
Pressione di esercizio max.: 250 bar  
Peso: 22.901.161 1.6 kg - 22.1617.11 22.1617.73 1.0 kg  
Lunghezza: 22.901.161 720 mm - 22.1617.11 22.1617.73 520 mm  
Portata massima impugnatura: 30 l/min

**Materiali:** ottone - acciaio inox - materiali plastici ad alta resistenza

**Impiego:** lavaggio in agricoltura ed industria fino a 100°C. Ugello protetto dagli urti. Angolo di spruzzo regolabile in continuo mediante l'impugnatura anteriore. Il sotto insieme lavaggio può essere assemblato alle più diffuse impugnature per ottenere la regolazione continua dell'angolo di spruzzo. La 22.901.161 è dotata di fermo di sicurezza della leva contro le aperture accidentali e di protezione per la mano dell'operatore a norma ISO/EN.

- 22.901.161** standard with M15x1 spray tip Ø1.5 - 1/2" BSPM. connection
- 22.1617.11** standard without spray tip - 1/4" BSPM. connection for washing handles manufactured by PA-ETL M15x1 spray tip connection
- 22.1617.73** standard without spray tip - 1/4" BSPM. connection for washing handles manufactured by Mecline M15x1 spray tip connection

Max. spray tip hole: Ø2.3  
Max. operating pressure: 250 bar / 3625 psi  
Weight: 22.901.161 1.6 kg / 3.5 lb - 22.1617.11 22.1617.73 1.0 kg / 2.2 lb  
Length: 22.901.161 720 mm / 28.3" - 22.1617.11 22.1617.73 520 mm / 20.5"  
Handle max. flow rate: 30 l/min - 8 USGal/min

**Materials:** brass - stainless steel - high resistance plastic materials

**Use:** high pressure spraying and washing up to 212°F. Spray tip shock proof protection. Front handle for easy spray pattern adjustment. The washing subassembly fits most of 1/4" BSPF. washing handles to obtain a continuous spray pattern adjustment. The 22.901.161 hand shield and trigger lock prevents accidental opening according to ISO/EN safety rules.

## COME SI ORDINA / HOW TO ORDER

CODICE code		KIT RICAMBIO spare parts kit
22.901.161	5	22.302.27
22.1617.11	5	
22.1617.73	5	



LANCE  
SPRAY GUNS



RACCORDI  
CONNECTIONS



LAVAGGIO  
WASHING



CATALOGHI  
CATALOGUES



IMMAGINI  
HI-RES PICTURES



RICAMBI  
SPARE PARTS :

22.901.161  
22.1617.11  
22.1617.73