



VALVOLE M29 - M30 M29 - M30 TRIGGER VALVES



◀ PAGE 18/25 ▶

Versioni standard:

M29: entrata G1/2M. o G1/2F. - guarnizioni in FPM - sede e pistone di tenuta in acciaio inox

M30: entrata G1/2M. o G1/2F. - guarnizioni in NBR - sede in materiale plastico ad alta resistenza - sfera di tenuta in acciaio inox.

Pressione di esercizio max: M29 / 50 bar - M30 / 20 bar

Peso: 200 g

Portata max.: 70 l/min

Materiali: materiali plastici ad alta resistenza - componenti in ottone e acciaio inox.

Impiego: valvole on/off. Eccellente resistenza ai prodotti chimici ed alla pressione. Ideale per l'impiego agricolo (diserbo localizzato) e industriale (nebulizzazione soluzioni oleose e lavaggio). Ottimo comfort per l'operatore.

Standard models:

M29: 1/2" BSPM. or 1/2" BSPF. inlet - FKM gaskets - stainless steel seat and shut off piston.

M30: 1/2" BSPM. or 1/2" BSPF. inlet - Buna N gaskets - high resistance plastic seat - stainless steel shut off ball.

Max. operating pressure: M29: 50 bar / 700 psi

M30: 20 bar / 300 psi

Weight: 200 g / 0.45 lb

Max. capacity: 70 l/min - 18.5 USGal/min

Materials: high resistance plastic materials - brass and stainless steel parts.

Use: on/off trigger with excellent corrosion and pressure resistance. Suitable for spot spraying in agriculture and for industrial applications (lubrication, nebulization and washing). Comfortable palm fitting.

COME SI ORDINA / HOW TO ORDER

CODICE code	ATTACCO connections		KIT RICAMBIO spare parts kit
29.1903.7	G1/2M-G1/2F.	10	29.302.24
30.1903.6	1/2" BSPM-1/2" BSPF.	10	30.302.25
29.1903.9	G1/2F-G1/2F.	10	29.302.24
30.1903.8	1/2" BSPF-1/2" BSPF.	10	30.302.25



LANCE
SPRAY GUNS



UGELLI
SPRAY TIPS



RACCORDI
CONNECTIONS



CATALOGHI
CATALOGUES



IMMAGINI
HI-RES PICTURES



RICAMBI
SPARE PARTS :

29.1903.7
29.1903.9

30.1903.6
30.1903.8