



VALVOLA M23 M23 TRIGGER VALVE



◀ PAGE 19/25 ▶

Versioni: con attacco G1/2F.
con attacco G1/2M.

Pressione di esercizio max: 50 bar
Peso: G1/2M. G1/2F. 340 g – G1/2F. G1/2F. 300 g
Portata max.: 70 l/min

Materiali: alluminio con trattamento al nichel chimico - sede e pistone di tenuta in acciaio inox - ottone - tenute in FPM - materiali plastici ad alta resistenza.

Impiego: valvola on/off. In agricoltura come impugnatura per lance.
Impieghi industriali per lubrificazione a pressione. Protezione per la mano dell'operatore.

Models: with 1/2" BSPF. connection
with 1/2" BSPM. connection

Max. operating pressure: 50 bar / 700 psi
Weight: 1/2" BSPM. 1/2" BSPF. 340 g / 12 oz
1/2" BSPF. 1/2" BSPF. 300 g / 10.6 oz
Max. capacity: 70 l/min - 18.5 USGal/min

Materials: Niploy processed aluminum body - stainless steel seat and shut off piston - brass - FKM gaskets - high resistance plastic materials.

Use: On/off valve. For agricultural and industrial use like oiling and greasing. Hand shield.

COME SI ORDINA / HOW TO ORDER

| CODICE code | ATTACCO connections |  | KIT RICAMBIO spare parts kit |
|-------------------|--------------------------------------|---|---------------------------------------|
| 23.208.84 | G1/2M-G1/2F. 1/2" BSPM-1/2" BSPF. | 10 | 23.302.26 |
| 23.1903.11 | G1/2F-G1/2F. 1/2" BSPF-1/2" BSPF. | 10 | 23.302.26 |



LANCE
SPRAY GUNS



UGELLI
SPRAY TIPS



RACCORDI
CONNECTIONS



CATALOGHI
CATALOGUES



IMMAGINI
HI-RES PICTURES



RICAMBI
SPARE PARTS :

23.208.84
23.1903.11